



AquesGlaze Exterior BU Glaze Paste

609-DVN-027

AquesGlaze Exterior BU Glaze Paste is an exterior water-based glaze pigment concentrates paste which designed for tinting with AquesGlaze Reducer to give richness and depth of color to the end grain. It can provide an antique looking or highlight with wiping on/off or dry brush to the finished wood.

TECHNICAL DATA:

Type	Water based
Code Number	609-DVN-027
Color	Burnt Umber (BU)
Flash Point	> 100°C
Specific Gravity	1.19 ± 0.05
Solids by Weight	35.41 ± 1.00%
Virgin Viscosity	120-130 KU by Stormer at 25°C
Mixing Ratio	1 part of AquesGlaze color paste 1 part of AquesGlaze reducer 50-XVN-5131.
Dry Schedule	30 - 45 minutes oven at 40-50°C
Storage Temperature	5 - 40°C
Relative Humidity	Optimum range 40-75%
Method of Application	Wiping by rag, brush and spraying
Directions for Use	The AquesGlaze Color Paste is to be <u>STIRRED WELL</u> before use and need to be reduced with AquesGlaze reducer.
Shelf Life	6 months in sealed container under shelter
Note	Film build for the entire finishing system including repairs should not exceed 4 dry mils

2018-Oct-22 V1

All information in this technical data sheets are based on our present knowledge derived from products test and history. It may vary in different situations. Actual dilution rates and viscosities may vary due to specific customer requirements or application processes. Please contact the Technical Department for more clarifications.